

WHAT IS CLAIMED IS:

1 1. A fixture adapted to combine with a drum stand which has a bracket having
2 two legs extending out from the bracket, a paddle having a first distal end connected to
3 the drum stand and a base having a first distal end connected to the bracket and a second
4 distal end securely connected to the paddle, the fixture comprising:

5 a pair of rods threadingly extendable into opposite sides of the first distal end of
6 the base, a pair of ribs adapted to be formed on opposite sides of the base, a pair of
7 guiding grooves adapted to be oppositely defined in a bottom portion of the bracket of
8 the drum stand to correspond to and receive therein the pair of ribs and a pair of notches
9 adapted to be oppositely defined in a mediate portion of the bracket of the drum stand to
10 correspond to and receive therein the pair of rods.

11 2. The fixture as claimed in claim 1, wherein the pair of rods are threaded bolts.

12 3. A fixture adapted to combine with a drum stand which has a bracket having
13 two legs extending out from the bracket, a paddle having a first distal end connected to
14 the drum stand and a base having a first distal end connected to the bracket and a second
15 distal end securely connected to the paddle, the fixture comprising:

16 a pair of guiding grooves oppositely defined in a bottom portion of the base, a
17 pair of notches oppositely defined in a mediate portion of the base, a pair of ribs formed
18 on a bottom portion of the bracket to correspond to and receive therein the ribs and a pair
19 of rods formed on a mediate portion of the bracket to correspond to and receive therein
20 the notches.

21 4. The fixture as claimed in claim 3, wherein the pair of rods are threaded bolts.